

### 6SL32101PH314AL0

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl32101ph314al0
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Product ID	6SL3210-1PH31-4AL0
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.01.2017
Configurable Product	False
Country of Origin	Germany
ECCN	9N9999
ETIM 7	EC001857
Group Classification Key	R220
List of Characteristics	D11.1SD
Packaging Size	MM
REACH	Lead CAS-Nr. 7439-92-1
Unit of Measure	ST
Customs Tariff Code	85044095
EAN	4042948668498
eClass 6	27-02-31-01
eClass 7.1	27-02-31-01
eClass 8	27-02-31-01
eClass Version 9	27-02-31-01
eClass Version 9.1	27-02-31-01
Quantity in Package	1
Packaging Length	745,00
Packaging Width	469,00
Packaging Height	385,00
Product Code	9775
Comparative Metals Coefficient	01.01.2017
Weight	65000 kg
Article Number	6SL32101PH314AL0
Product Family	Power Modules
Catalog ID	D11.1SD
Packaging Dimensions	18.465 x 29.331 x 15.157
Package Size Unit of Measure	Inch
Quantity Unit	1 Piece
Voltage Rating	690 V
Power	110, 132 kW
Frequency Range	47 - 63 Hz

<b>IP Rating</b>	IP20
<b>Product Group</b>	9775
<b>Net Weight</b>	143.300 lb
<b>Packaging Quantity</b>	1 pieces
<b>Commodity Code</b>	85044088

## Description

SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 110KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 132kW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (LO) 708 X 305 X 357 (HXWXD), FSF PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 HF8