

6SL32101RE311UL0

Industrial automation components

| | |
|-----------------------|----------------------------------|
| Manufacturer | Siemens |
| Catalog number | 6sl32101re311ul0 |
| Category | Industrial automation components |
| Product type | Industrial automation components |
| Status | Active product |

Technical specification

| | |
|--------------------------------|--------------------------------------|
| Product ID | 6SL3210-1RE31-1UL0 |
| Notes | Wycofanie produktu od: 01.10.2023 |
| AL Field | N |
| Compliance | Produkt zgodny z RoHS od: 22.12.2016 |
| Configurable Product | False |
| Country of Origin | DE |
| ECCN | 9N9999 |
| ETIM 7 | EC001857 |
| Group Classification Key | R220 |
| List of Characteristics | D11.1SD |
| Packaging Size | MM |
| REACH | Lead CAS-Nr. 7439-92-1 |
| Unit of Measure | ST |
| Customs Tariff Code | 85044086 |
| EAN | 4042948673454.0 |
| eClass 6 | 27-02-31-01 |
| eClass 7.1 | 27-02-31-01 |
| eClass 8 | 27-02-31-01 |
| eClass Version 9 | 27-02-31-01 |
| eClass Version 9.1 | 27-02-31-01 |
| Quantity in Package | 1 |
| Packaging Length | 595,00 |
| Packaging Width | 400,00 |
| Packaging Height | 350,00 |
| Product Code | 5678 |
| Comparative Metals Coefficient | 22.12.2016 |
| UPC | 804766373053.0 |
| Weight | 26400 kg |

Description

SINAMICS G120 POWER MODULE PM240P-2 UNFILTERED 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 150% 60S, 100% 240S; AMBIENT TEMP -20 TO +50 DEG C (H0) OUTPUT LOW OVERLOAD: 55kw FOR 135% 3S,110% 57S,100% 240S AMBIENT TEMP -20 TO +40 DEG C (L0) 551x 275x 237 (HXWXD), FSE PROTECTION IP20 WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU FIRMWARE- VERSION V4.7 SP6 HF1