

## 6SL3211-0AB12-5UA1

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3211-0ab12-5ua1
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

### Technical specification

<b>Weight</b>	0.32 kgs
<b>Power</b>	0.25
<b>Component Specifications</b>	cpm110
<b>Temperature</b>	50
<b>Cable Specification</b>	90 × 116
<b>I/O Channels</b>	150 channels
<b>Signal Type</b>	240
<b>Signal Level</b>	240 V
<b>Relay Specifications</b>	240 VAC
<b>Voltage</b>	AC
<b>Cooling Capacity</b>	0.25
<b>Product Type</b>	Drive
<b>Manufacturer</b>	Siemens
<b>Industrial System</b>	sinamics
<b>I/O Configuration</b>	150

### Description

6SL3211-0AB12-5UA1 | Siemens, AC Drive, 4.5 A, 200 to 240 V ac, 0.25 kW (Output), 90 mm, 116 mm, 150 mm | Brand / Manufacturer: Siemens | product type: AC Drive | number of phases: 1 | current rating: 4.5 A | supply voltage: 200 to 240 V ac | power classification: 0.25 kW (Output) | frequency classification: 47 to 63 Hz | level of security: IP20 | minimum operating temperature: -10 °C | maximum working temperature: +40 °C | Total length: 90 mm | total width: 116 mm | total height: 150 mm | type of communication port: RS485 | mass: 0.7 kg