

### 6SL3243-0BB30-1HA3

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl3243-0bb30-1ha3
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	0.28 kgs
<b>Product ID</b>	6SL3243-0BB30-1HA3
<b>AL Field</b>	N
<b>Customs Tariff Code</b>	85049090
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.07.2006
<b>Configurable Product</b>	False
<b>Country of Origin</b>	GB
<b>EAN</b>	4042948665879.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-02-31-01
<b>eClass 7.1</b>	27-02-31-01
<b>eClass 8</b>	27-02-31-01
<b>eClass Version 9</b>	27-02-31-01
<b>eClass Version 9.1</b>	27-02-31-50
<b>ETIM 7</b>	EC001857
<b>Group Classification Key</b>	R220
<b>List of Characteristics</b>	D11.1SD
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	215,00
<b>Packaging Width</b>	100,00
<b>Packaging Height</b>	100,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	SINAMICS G120 Control Unit CU230P-2 HVAC USS/MODBUS RTU/BACnet MS/TP 6 DI, 3 DO, 4 AI, 2 AO 1 motor temperature sensor input 2 PSU-out (10 V DC, 24 V DC) 1 PSU-in (24 V DC) USB and MMC interface Degree of protection IP20
<b>Product Code</b>	9778
<b>Comparative Metals Coefficient</b>	01.07.2006
<b>REACH</b>	Lead CAS-Nr. 7439-92-1
<b>Unit of Measure</b>	ST
<b>UPC</b>	887621270681.0

## Description

6SL3243-0BB30-1HA3 | Siemens, SINAMICS G120 Series, Inverter Drive, 0.37 to 250 kW, 20 to 29 V dc, 0.50 A, IP20 | Brand / Manufacturer: Siemens | height: 215 | width: 100 | depth: 100 | product type: Inverter Drive | power classification: 0.37 to 250 kW | supply voltage: 20 to 29 V dc | current rating: 0.50 A | output frequency: 0 to 200 Hz (Vector Control);0 to 650 Hz (V/F Control) | ambient temperature: -10 to +60 °C | filter included yes / no: No | function: Variable Frequency Flux Current Control;Vector Control | series: SINAMICS G120 | level of security: IP20 | type of attachment: Screw Mount | Power assessment in horsepower: 0.5 to 400 hp | Size: 73.0 x 199.0 x 65.5 mm | requirements met: Low-voltage directive 2014/35/EC;CE, UL, cUL, RCM, SEMI F47 | mass: 0.61 kg