

### 6SL33301TE412AA3

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl33301te412aa3
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

Weight	320000 kg
Customs Tariff Code	85044083
eClass 6	27-02-31-01
eClass 7.1	27-02-31-01
eClass 8	27-02-31-01
eClass Version 9	27-02-31-01
eClass Version 9.1	27-02-31-01
Quantity in Package	1
Packaging Length	0,00
Packaging Width	0,00
Packaging Height	0,00
Product Code	4926
Comparative Metals Coefficient	01.08.2018
UPC	40892557404.0
Product ID	6SL3330-1TE41-2AA3
AL Field	N
Compliance	Produkt zgodny z RoHS od: 01.08.2018
Configurable Product	True
Country of Origin	DE
ECCN	N
ETIM 7	EC001857
Group Classification Key	R220
List of Characteristics	D21.1LD
Product Description	SINAMICS S120 basic line module 380-480V 3AC, 50/60 Hz, 1200A Output: 510-650 V DC Type rating: 560kW Built-in unit IP00 design CIM Internal air cooling incl. Drive-CLiQ cable
REACH	Lead CAS-Nr. 7439-92-1; Dodecachloropentacyclo[12.2.1.1 6,9.02,13.05,10]octadeca-7,15-diene ("Dechlorane Plus™") covering any of its individual anti- and syn-isomers or any combination thereof lblREACHCasNo0007
Unit of Measure	ST

## Description

The SINAMICS S120 basic line module operates at a voltage of 380-480V 3AC, 50/60 Hz, with a maximum output current of 1200A and a voltage range of 510-650 V DC. It is rated for 560kW and features an IP00 design. The built-in unit includes internal air cooling and a Drive-CLiQ cable. This product is RoHS compliant since 01.08.2018 and is configurable. The weight is 65.79 kg, and it is manufactured in Germany.