

### 6SL33307TE410AA3

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6sl33307te410aa3
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	438000 kg
<b>Customs Tariff Code</b>	85044083
<b>eClass 6</b>	27-02-31-01
<b>eClass 7.1</b>	27-02-31-01
<b>eClass 8</b>	27-02-31-01
<b>eClass Version 9</b>	27-02-31-01
<b>eClass Version 9.1</b>	27-02-31-01
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	0,00
<b>Packaging Width</b>	0,00
<b>Packaging Height</b>	0,00
<b>Product Code</b>	4926
<b>Comparative Metals Coefficient</b>	01.08.2018
<b>UPC</b>	40892556919.0
<b>Product ID</b>	6SL3330-7TE41-0AA3
<b>AL Field</b>	N
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.08.2018
<b>Configurable Product</b>	True
<b>Country of Origin</b>	DE
<b>ECCN</b>	N
<b>ETIM 7</b>	EC001857
<b>Group Classification Key</b>	R220
<b>List of Characteristics</b>	D21LD
<b>Product Description</b>	SINAMICS Active Line Module 380-480V 3AC, 50/60 Hz, 985A Output: 510-720 V DC Rated power: 630kW Built-in unit IP00 design CIM Internal air cooling incl. Drive-CLiQ cable
<b>Unit of Measure</b>	ST

## Description

The SINAMICS Active Line Module operates at a voltage of 380-480V 3AC, 50/60 Hz, with an output of 985A and a rated voltage of 510-720 V DC. It has a rated power of 630kW and features a built-in unit with an IP00 design and internal air cooling, including a Drive-CLiQ cable. Compliant with RoHS since 01.08.2018, this configurable product is manufactured in Germany and weighs 186.00 kg, with a customs tariff code of 85044083.