

6SL37301TG418CU3

Industrial automation components

Manufacturer	Siemens
Catalog number	6sl37301tg418cu3
Category	Industrial automation components
Product type	Industrial automation components
Status	Active product

Technical specification

Customs Tariff Code	85044086
eClass 6	27-02-31-01
eClass 7.1	27-02-31-01
eClass 8	27-02-31-01
eClass Version 9	27-02-31-01
eClass Version 9.1	27-02-31-01
Quantity in Package	1
Packaging Length	0,00
Packaging Width	0,00
Packaging Height	0,00
Product Code	4924
Comparative Metals Coefficient	22.07.2019
Weight	440000 kg
Product ID	6SL3730-1TG41-8CU3
AL Field	N
Compliance	Produkt zgodny z RoHS od: 22.07.2019
Configurable Product	True
Country of Origin	Germany
ECCN	N
ETIM 7	EC001857
Group Classification Key	P122
List of Characteristics	D21.3LD
REACH	Lead CAS-Nr. 7439-92-1; Dodecachloropentacyclo[12.2.1.1.1 6,9.02,13.05,10]octadeca-7,15-diene ("Dechlorane Plus™") covering any of its individual anti- and syn-isomers or any combination thereof lblREACHCasNo0007
Unit of Measure	ST
Product Description	SINAMICS S120 CABINET MODULE BASIC LINE MODULE 3AC 500-690V, 50/60HZ, 1880A OUTPUT: DC 675 - 930V UNIT RATING: 1500KW CUBICLE UNIT IP20 AIR COOLING, VERSION FOR PARALLEL CONNECTION, MOUNTING ON THE LEFT TO LCM, NEMA DESIGN
Article Number	6SL37301TG418CU3
Voltage Rating	690 V, 930 V
Frequency Range	50 - 60 Hz
IP Rating	IP20
Product Family	Ordering Data Overview

Product Group	4924
Catalog ID	D21.3LD
Net Weight	970.034 lb
Quantity Unit	1 Piece
Packaging Quantity	1 pieces
Commodity Code	85044088
Current Rating	1880 A
Power	1500 kW

Description

The SINAMICS S120 CABINET BASIC LINE MODULE operates at 3AC 500-690V, 50/60Hz with a current rating of 1880A and a DC output range of 675-930V. It is rated for 1500kW, features IP20 protection, and utilizes air cooling. This unit is designed for parallel connections and is mounted on the left side of the LCM, adhering to NEMA design standards.