

### 6SL5510-1BE11-5AF0

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | 6sl5510-1be11-5af0               |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Customs Tariff Code            | 85044095  |
| EAN                            | 4034106445652.0   |
| Quantity in Package            | 1   |
| Packaging Length               | 237,00  |
| Packaging Width                | 99,00   |
| Packaging Height               | 249,00  |
| Comparative Metals Coefficient | 23.11.2021  |
| UPC                            | 195125457546.0  |
| Weight                         | 2010 kg   |
| Product ID                     | 6SL5510-1BE11-5AF0  |
| AL Field                       | N   |
| Compliance                     | Produkt zgodny z RoHS od: 23.11.2021  |
| Configurable Product           | False   |
| Country of Origin              | CN  |
| ECCN                           | N   |
| Group Classification Key       | R220  |
| List of Characteristics        | SINAMICS S200   |
| Packaging Size                 | MM  |
| Product Description            | SINAMICS S200, with PROFINET Input voltage: 380-480 V 3AC; -15%/+10%; 5.5A; 50/60Hz; Output voltage: 0-inpu 5.3A; 0-550Hz; Motor: 1.75kW Degree of protection: IP20 FSC, 90x180x200 (WxHxD) |
| Product Code                   | X0H6  |
| REACH                          | Lead CAS-Nr. 7439-92-1; Lead monoxide (lead oxide) lblREACHCasNo7368; 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-Nr. 80-05-7; Silicic acid, lead salt lblREACHCasNo4420             |
| Unit of Measure                | ST  |

## Description

SINAMICS S200, with PROFINET input. Input voltage: 380-480 V 3AC; -15%/+10%; 5.5A; 50/60Hz; Output voltage: 0-5.3A; 0-550Hz; Motor: 1.75kW. Degree of protection: IP20 FSC, 90x180x200 (WxHxD).