

### 6XV1440-4BN25

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	6xv1440-4bn25
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Legacy / discontinued

## Technical specification

Weight	2.72 kgs
Product ID	6XV1440-4BN25
AL Field	N
Customs Tariff Code	85444290
Compliance	Produkt zgodny z RoHS od: 27.08.2013
Configurable Product	False
Country of Origin	HU
EAN	4025515089964.0
ECCN	N
eClass 6	27-24-92-03
eClass 7.1	27-24-92-03
eClass 8	27-24-92-03
eClass Version 9	27-33-02-92
eClass Version 9.1	27-33-02-92
ETIM 7	EC002584
Group Classification Key	R141
List of Characteristics	ST80.1Q
Quantity in Package	1
Packaging Length	32,00
Packaging Width	28,00
Packaging Height	8,30
Packaging Size	CM
Product Description	Connecting cable PN for Mobile Panels (PROFINET), Length 25 m
Product Code	2260
Comparative Metals Coefficient	27.08.2013
REACH	Imidazolidine-2-thione (2-imidazoline-2-thiol) lblREACHCasNo4360
Unit of Measure	ST
UPC	662643256888.0

## Description

6XV1440-4BN25 | Siemens, Connecting Cable for Mobile Panel, 24 V dc, 25 m (Length)9 mm (Diameter) | Brand / Manufacturer: Siemens | mass: 3.084 | product type: Connecting Cable | input voltage: 24 V dc | for use with: Mobile Panel | Material: Polyurethane | length: 25 m | width: 9 mm (Dia.) | minimum operating temperature: 0 °C | maximum working temperature: +55 °C