

### 8US1210-4AG00

Industrial automation components

<b>Manufacturer</b>	Siemens
<b>Catalog number</b>	8us1210-4ag00
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

## Technical specification

<b>Weight</b>	2.72 kgs
<b>Product ID</b>	8US1210-4AG00
<b>AL Field</b>	N
<b>Aluminium Weight</b>	0
<b>Argent Weight</b>	0
<b>Customs Tariff Code</b>	85389099
<b>Compliance</b>	Produkt zgodny z RoHS od: 01.01.2003
<b>Configurable Product</b>	False
<b>Copper Weight</b>	0
<b>Country of Origin</b>	DE
<b>EAN</b>	4011209125445.0
<b>ECCN</b>	N
<b>eClass 6</b>	27-37-03-01
<b>eClass 7.1</b>	27-37-03-01
<b>eClass 8</b>	27-37-03-01
<b>eClass Version 9</b>	27-37-03-01
<b>eClass Version 9.1</b>	27-37-03-01
<b>ETIM 7</b>	EC001531
<b>Group Classification Key</b>	P360
<b>List of Characteristics</b>	LV10.1
<b>Metals Coefficient</b>	L-P-----
<b>Quantity in Package</b>	1
<b>Packaging Length</b>	330,00
<b>Packaging Width</b>	266,00
<b>Packaging Height</b>	86,00
<b>Packaging Size</b>	MM
<b>Product Description</b>	system szyn zbiorczych Odstęp między osiami szyn 60mm, Adapter urządzeniowy, Szerokość 250 mm Grubość szyny: 5,10mm+profil TT do aparatury rozdzielczej do 630A 3NP52/53/54
<b>Product Code</b>	5888
<b>Comparative Metals Coefficient</b>	01.01.2003
<b>Unit of Measure</b>	ST
<b>UPC</b>	754554472003.0