

### BVP:610411

Industrial automation components

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Manufacturer</b>   | Siemens                          |
| <b>Catalog number</b> | bvp610411                        |
| <b>Category</b>       | Industrial automation components |
| <b>Product type</b>   | Industrial automation components |
| <b>Status</b>         | Active product                   |

## Technical specification

|                                |   |
|--------------------------------|---|
| Argent Weight                  | 0   |
| Customs Tariff Code            | 85369001  |
| EAN                            | 4019169810043.0   |
| Quantity in Package            | 1   |
| Product Code                   | 3732  |
| Weight                         | 30000   |
| Product ID                     | BVP:610411  |
| AL Field                       | N   |
| Aluminium Weight               | 0,520   |
| Aluminium Weight Unit          | KG  |
| Compliance                     | Produkt zgodny z RoHS od: 01.07.2006  |
| Configurable Product           | False   |
| Copper Weight                  | 0,510   |
| Copper Weight Unit             | KG  |
| Country of Origin              | CZ  |
| ECCN                           | N   |
| eClass 6                       | 27-14-27-02   |
| eClass 7.1                     | 27-14-27-02   |
| eClass 8                       | 27-14-27-02   |
| eClass Version 9               | 27-14-27-02   |
| eClass Version 9.1             | 27-14-27-02   |
| ETIM 7                         | EC000008  |
| Group Classification Key       | P374  |
| List of Characteristics        | LV10.2  |
| Metals Coefficient             | --33----  |
| Packaging Length               | 725,00  |
| Packaging Width                | 494,00  |
| Packaging Height               | 336,00  |
| Packaging Size                 | MM  |
| Product Description            | SKRZYŃKA ODPIYOWA, ZACISK ŚRUBOWY, IE=250A, UE=400V / 1X 3 BIEG., GNIAZDO BEZP. NH1/ ROZŁ. BEZPIECZNIKOWY BS. MAKS. PRĄD WKŁADKI = 225A |
| Comparative Metals Coefficient | 01.07.2006  |
| Unit of Measure                | ST  |