

### ATS46D32N

Industrial automation components

<b>Manufacturer</b>	Telemecanique
<b>Catalog number</b>	ats46d32n
<b>Category</b>	Industrial automation components
<b>Product type</b>	Industrial automation components
<b>Status</b>	Active product

### Technical specification

<b>Weight</b>	1.86 kgs
<b>Current</b>	32 A
<b>Frequency</b>	50 - 60 Hz
<b>Signal Type</b>	500
<b>Signal Level</b>	500 V
<b>Relay Specifications</b>	500 VAC
<b>Voltage</b>	220 - 500 V
<b>Power</b>	15 kW
<b>Cooling Capacity</b>	15 kW
<b>Product Type</b>	Drive

### Description

ATS46D32N | Telemecanique, Soft Starter, Soft Starter, 7.5 kW, 230 to 415 V ac, 55 A, '3 Phase, 47.5 Hz, 63 Hz, Screw Mount, Screw Terminal | Brand / Manufacturer: Telemecanique | product type: Soft Starter | type of motor starter: Soft Starter | power classification: 7.5 kW | control voltage: 230 to 415 V ac | current rating: 55 A | phase: 3 | minimum operating frequency: 47.5 Hz | maximum operating frequency: 63 Hz | type of attachment: Screw Mount | voltage on terminals: Screw | minimum operating temperature: 0 °C | maximum working temperature: +55 °C | Total length: 160 mm | total width: 190 mm | overall depth: 275 mm